



JETAIRE® 30 TON MOBILE PRE-CONDITIONED AIR UNITS



SPECIFICATIONS _

DESIGN ELEMENTS

Jetaire® Mobile Pre-conditioned Air Units offer maximum economy and dependability.

Mounted on an integrated trailer and powered by a robust diesel engine and generator set, the mobile units have become the best solution to keep aircraft interiors comfortable in hangars, at maintenance sites, and on the ramp.

Jetaire® 30 Ton mobile units offer high energy efficiency ratios (EER) and service a variety of aircraft.

Jetaire® 30 Ton mobile may also operate using building-supplied power.

ENGINE/GENERATOR SET

Unit 30 Ton

Diesel EngineCummins QSB4.5-G3GeneratorNewage 80 kWEngine/Generator ControllerIFM PLC

Fuel Capacity/Running Time 60 gal./8 hours (227 L.)

DIMENSIONS/WEIGHT

Unit 30 Tor

 Length
 157 in (398.78 cm)

 Width
 88 in (223.52 cm)

 Height
 84 in (213.36 cm)

 Weight
 8,000 lbs

CONTROL SYSTEM

Unit 30 Ton Controls PLC

BIOWFR

 Unit
 30 Ton

 Blower
 Motor 25 hp

 Air Flow
 200 lb/min

 Static Pressure
 27.7 in

CONDENSER FANS

Unit 30 Ton Quantity Per Unit 3 Fan Motors 3 hp

Diameter 30 in (76.2 cm)

COMPRESSORS

Unit30 TonQuantity Per Unit2Refrigeration Capacity15 TonsRefrigerantR407CManufacturerDanfoss

CONDENSER COILS

 Unit
 30 Ton

 Rows Per
 Unit 3

 Finned Height
 36 in [91.4 cm]

 Finned Length
 110 in [279.4 cm]

EVAPORATOR COILS

Unit 30 Ton Rows Per Unit 7

 Finned Height
 30 in (76.2 cm)

 Finned Length
 43.5 in (110.5 cm)

DESIGN AMBIENT

 Unit
 30 Ton

 Humid - Dry Bulb
 97° F [36.1° C]

 Humid - Wet Bulb
 85° F [29.5° C]

 Dry - Dry Bulb
 125° F [51.7° C]

 Dry - Wet Bulb
 65° F [18.3° C]

SOUND LEVEL

80 dBA @ 15 ft (4.6 m)

STANDARD EQUIPMENT

- → Programmable Logic Controls
- → Diesel Engine and Generator Set
- → Dual Hose Outlets (8-inch)
- → Ackerman Steering
- → Hand operated Parking Brake
- → Hose Storage Compartment
- → 25 hp Blower Motor
- → Running Gear with Pneumatic Tires
- → Leaf -Spring Suspension

AIRCRAFT SERVICED

- → Military
- → C 130
- → C-17
- → C-5

